

# Newly updated versions with superior air flow capacity.

The Bronze series expands by introducing the new 60H+ HRV: an air exchanger with heat recovery, ENERGY STAR®\* certified in Canada. Also available with energy recovery, these models are providing up to 120 CFM. The smartest in their category.

An air exchanger as effective as it is versatile!

- State-of-the-art ventilation technology
- Ideal choice for condos, apartments, pre-fab houses and tract homes
- Low profile construction for ceiling mount in closet or above hot water tank
- Fast and versatile installation with top or side ports options
- Easy to balance with integrated dampers and pressure taps
- Now with a 5-year warranty



## Maintenance and installation made easy!

#### **Easy to Reach Filters**


Washable foam filters effectively filter airborne particles, such as pet dander, lint, dust and mold spores, while protecting the equipement from dust build-up.

#### HomeShield™ Defrosting System

Prevents ice build-up on recovery module without creating negative indoor air pressure.

**Flexible Port Configuration** 

Versatile design allows for vertical or horizontal port configuration, facilitating installation and maintenance. (Factory-configured)



## **Removable Electrical Drawer**

Remove one screw to release and access the electronics with pull out PCB assembly for easy maintenance of major sub-compenents.

#### **Intelligent Flow Dampers**

The fresh air intake port is equipped with a damper controlled by an intelligent motor with integrated circuit logic Easy to access. Easy to maintain. Very precise.



#### **High-Pressure Blower**

Designed to eliminate the need to balance unit in most simple installations.

#### **Bottom Door Opening**

Unique bottom door opening design allows parallel duct connection for easy access from any angle.

#### **Patented Balancing System**

Patented pressure taps eliminate the need for an external flow meter and reduce installation

time.







Specifications	60H+ HRV	60H+ ERV	
Part number	41650 (Side Ports) 41652 (Top Ports)	41654 (Side Ports) 41656 (Top Ports)	
Maximum continuous air flow (at 0.2 in. w.g.)	126 CFM	130 CFM	
Maximum continuous air flow (at 0.4 in. w.g.)	115 CFM	120 CFM	
Sensible Recovery Efficiency @ 0°C	65%	67%	
Sensible Recovery Efficiency @ -25°C	60%	60%	
Total Recovery Efficiency @ 35°C	n/a	55%	
Dimensions	12 <sup>3</sup> /16 in. x 22 <sup>9</sup> /	12 <sup>3</sup> /16 in. x 22 <sup>9</sup> /16 in. x 19 <sup>13</sup> /16 in.	
Pressure taps to balance air flow	Yes	Yes	
Balancing dampers	Yes	Yes	
Fan efficacy	1.2 CFM/W	1.2 CFM/W	
Electrical consumption (low speed)	43 W	42 W	
Wall control compatibility	Simple-Touch, Deco-Touch, Lite-Touch, Bronze, Platinum	Simple-Touch, Deco-Touch, Lite-Touch, Bronze, Platinum	
Warranty on parts	5 years	5 years	
Warranty on core	Limited lifetime	5 years	
HVI CERTIFIED C UL US	Yes	Yes	
*  ENERGY STAR	Yes	Yes	

 $These \ specifications \ are \ subject \ to \ change \ without \ notice, \ please \ see \ the \ specification \ sheet \ on \ www.vanee.ca.$ 

### Available at this authorized dealer:



<sup>\*</sup> This product earned the ENERGY STAR® by meeting strict energy efficiency guidelines set by Natural Resources Canada and the US EPA. It meets ENERGY STAR® requirements only when used in Canada.